




Male Adapter

Mipt x Socket




Part Number	Size	L	M1	N	Approx. Wt. (Lbs.)
836-053	3/8X1/2	1-11/16	1- 3/16	1/4	.03
836-005	1/2	1-23/32	1- 5/32	3/16	.03
836-007	3/4	1-27/32	1- 7/16	7/32	.05
836-102	3/4X1	2- 9/32	1- 3/4	17/32	.09
836-131	1X3/4	2- 1/16	1-13/32	1/4	.06
836-010	1	2- 5/32	1-23/32	7/32	.09
836-012	1-1/4	2- 1/4	2- 1/8	1/32	.14
836-015	1-1/2	2-11/16	2- 3/8	9/32	.18
836-251 ¹	2X1-1/2	3- 3/32	2-29/32	19/32	.42
836-020	2	2- 7/8	2- 7/8	5/16	.28
836-025	2-1/2	3-21/32	3-17/32	11/32	.52
836-030	3	3- 7/8	4- 1/4	3/8	.74
836-040	4	4-13/32	5- 5/16	13/32	1.14
836-050F	5	6	6- 5/16	1- 5/8	2.07
836-060	6	5- 1/2	7- 9/16	19/32	2.88
836-080F	8	8- 3/16	9- 5/8	2- 3/16	4.54
836-100F	10	10- 3/8	11-15/16	3- 3/16	11.95
836-120F	12	11- 1/8	14- 1/8	2- 3/4	20.94

1- Sized With Bushing

Male Adapter - Internal Reinforced

Mipt x Socket - Stainless Steel Sleeve
NSF® Certified Lead Free



Part Number	Size	L	M1	N	Approx. Wt. (Lbs.)
836-005R	1/2	2- 3/32	1- 5/32	9/16	.05
836-007R	3/4	2- 1/4	1- 3/8	9/16	.08
836-010R	1	2-21/32	1-23/32	11/16	.14