




**Reducer Bushing (T.T.)
Flush Style**

Mipt x Fipt




(Continued)

Part Number	Size	L	N	Approx. Wt. (Lbs.)
839-422	4X3	2- 1/8	1/2	.71
839-532	6X4	3-17/32	1- 13/16	2.53

**Reducer Bushing -
Special Reinforced**


Mipt x SR Fipt - Stainless Steel Collar



Part Number	Size	L	N	Approx. Wt. (Lbs.)
839-128SR	1X1/4	1- 1/8	17/32	.05
839-209SR	1-1/2X1/2	1-11/32	19/32	.12
839-210SR	1-1/2X3/4	1-11/32	19/32	.12
839-247SR	2X1/2	1- 3/8	21/32	.17
839-248SR	2X3/4	1- 3/8	5/8	.19
839-249SR	2X1	1- 3/8	15/32	.19
839-420SR	4X2	2- 1/8	1- 1/8	.87

Cap

Socket




Part Number	Size	M	W	Approx. Wt. (Lbs.)
847-002	1/4	13/16	15/16	.01
847-003	3/8	31/32	1- 1/8	.02
847-005	1/2	1- 3/16	1- 7/32	.03
847-007	3/4	1- 3/8	1-13/32	.04
847-010	1	1-23/32	1- 5/8	.07
847-012	1-1/4	2- 3/32	1-27/32	.12
847-015	1-1/2	2-11/32	2	.16
847-020	2	2-7/8	2- 1/4	.25
847-025	2-1/2	3-17/32	2- 5/8	.48



Schedule 80 Fittings


Cap
Socket

(Continued)



Part Number	Size	M	W	Approx. Wt. (Lbs.)
847-030	3	4- 5/32	3- 1/32	.70
847-040	4	5- 1/4	3-19/32	1.16
847-050F	5	6- 1/2	4- 7/16	1.85
847-060	6	7- 1/2	4- 7/8	3.11
847-080	8	9-23/32	6- 3/8	6.30
847-100F	10	12- 1/4	5-15/16	7.89
847-120F	12	14- 1/4	7- 1/8	11.29
847-140F	14	15- 1/2	7- 3/8	13.19
847-160F	16	17- 7/8	9	24.27
847-180F	18	19-15/16	9- 1/4	32.09
847-200F	20	22	14-1/4	49.04
847-240F	24	26- 3/8	17- 1/4	89.38

Cap
Fipt



Part Number	Size	M	W	Approx. Wt. (Lbs.)
848-002	1/4	29/32	15/16	.01
848-003	3/8	31/32	29/32	.01
848-005	1/2	1- 3/16	1- 1/16	.03
848-007	3/4	1- 3/8	1- 7/32	.04
848-010	1	1-27/32	1- 7/16	.10
848-012	1-1/4	2- 7/32	1-17/32	.14
848-015	1-1/2	2-17/32	1- 5/8	.19
848-020	2	3- 5/32	1-25/32	.28
848-025	2-1/2	3- 5/8	2- 7/16	.53
848-030	3	4- 3/8	2- 7/16	.75
848-040	4	5- 7/16	3- 1/16	1.32
848-060F	6	7- 3/16	4- 3/8	2.07
848-080F	8	9- 3/8	4- 3/8	3.52
848-100F	10	11-7/8	5-3/4	7.42
848-120F	12	13-13/16	6-3/16	10.77