




## Schedule 80 Unions

### Union 2000 - Special Reinforced Fipt/FKM

SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar

Dimensions Also Applicable to 8098-XXXSR EPDM O-Ring Seals




Pressure Rating  
1/2" - 4" 235 psi @ 73°F  
6" 150 PSI @ 73°F

Part Number	Size	L	M	N	NUT O.D.	Approx. Wt. (Lbs.)
8058-005SR	1/2	2	1- 3/16	5/8	1- 7/8	.14
8058-007SR	3/4	2- 5/32	1- 3/8	21/32	2- 9/32	.21
8058-010SR	1	2- 9/16	1-11/16	13/16	2- 9/16	.31
8058-012SR	1-1/4	2-23/32	2- 1/32	13/16	3- 1/8	.44
8058-015SR	1-1/2	2-27/32	2-13/32	29/32	3-17/32	.60
8058-020SR	2	3- 7/32	3- 1/32	1- 3/16	4- 7/32	.97
8058-025SR	2-1/2	4- 3/32	3- 9/16	1-15/32	6- 5/32	2.37
8058-030SR	3	4- 3/16	4- 9/32	1- 3/8	6- 5/32	2.49
8058-040SR	4	4-11/16	5- 1/4	1-11/16	7- 3/4	3.96
8058-060SR	6	6- 3/16	7-11/16	2-13/16	11- 5/8	12.05

### Union (Old Style) - Socket/FKM

Socket x Socket with FKM O-ring Seal

Dimensions Also Applicable to 897-XXX EPDM O-Ring Seals



Pressure Rating  
235 psi @ 73°F

Part Number	Size	L	M	N	NUT O.D.	Approx. Wt. (Lbs.)
857-005	1/2	2- 3/32	1- 9/32	11/32	1-31/32	.15
857-007	3/4	2- 3/8	1-17/32	11/32	2- 1/2	.26
857-010	1	2- 9/16	1-27/32	3/8	2- 7/8	.37
857-012	1-1/4	2- 7/8	2- 7/32	3/8	3- 5/16	.50
857-015	1-1/2	3- 3/32	2- 9/16	15/32	3- 9/16	.62
857-020	2	3- 5/8	3- 1/32	9/16	4- 3/16	.98
857-025	2-1/2	4- 3/8	3- 5/8	15/16	4- 7/8	1.50
857-030	3	5- 1/16	4- 3/8	1- 3/16	5- 3/4	2.35
857-040	4	5- 7/8	5-13/32	1- 3/8	7- 1/16	3.77